



+ PRODUCTS

- DC Inverter technology.
- Commercial application.



RC09

FEATURES

TECHNOLOGY:



DC INVERTER



R410A FLUID



ELECTRONIC EXPANSION VALVE

AIR QUALITY / CLEAN:



AIR FILTER



AUTO CLEAN/DRY

INSTALLER FUNCTIONS:



ERROR CODE VIA INDOOR UNIT





SELF DIAGNOSTIC



- High efficiency (SEER greater than 5) which brings energy savings throughout the year.
- Long blowing distance (up to 15m).
- Display and control screen on the unit.

COMBINATIONS

Indoor unit Floor standing	Compatible with outdoor unit Monosplit
<p>SDM</p> 	<p>YSDM</p> 

SDM

Floor standing

SDM TECHNICAL DATA

Indoor unit		AW-SDM048-N11
Outdoor unit		AW-YSDM048-H11
Phase		Single phase
COOLING		
Rated power (min./max.)	kW	12.5 (6.0-14.5)
Rated power input	kW	3.90 (2.0-6.0)
SEER/Energy label		5.1/A
Operating limits	°C	-10°/46° Dry bulb
HEATING		
Rated power (min./max.)	kW	13.0 (6.0-16.5)
Rated power input	kW	4.05 (2.0-6.0)
SCOP/Energy label		3.4/A
Operating limits	°C	-15°/24° Dry bulb
INDOOR UNIT		
Sound pressure level to 1.5 m (LS/MS/HS)	dB(A)	44/48/51
Sound power level	dB(A)	69
Airflow (LS/MS/HS)	m³/h	1350/1500/1750
Dehumidification	l/h	5
Outline dimensions (WxHxD)	mm	1850x600x350
Package dimensions (WxHxD)	mm	1986x691x415
Net weight/Gross weight	kg	57/65
Part number		7SP011088
OUTDOOR UNIT		
Sound pressure level to 1 m	dB(A)	59
Sound power level	dB(A)	73
Airflow	m³/h	4200
Compressor type		Twin rotary
Outline dimensions (WxHxD)	mm	1008x830x410
Package dimensions (WxHxD)	mm	1142x1000x498
Net weight/Gross weight	kg	82/93
Part number		7SP062971
POWER SUPPLY		
Phase/Tension/Frequency		1P/230V/50Hz
Power supply side		Extérieur
Power cable section	mm²	3x4
Fuse rating am (D curve)	A	25
Electrical connections	mm²	4x2.5
PIPE LINE		
Suction pipe diameter	inches	3/4"
Liquid pipe diameter	inches	3/8"
Max. length	m	50
Max. height	m	30
Refrigerant / GWP		R410A/2088
Charge (5m)	kg	2.85