



# F117/F127

ErP Ready\*\*

French quality active heat convector with user-friendly controls



## **COMFORT**

- Easy prog: 24h/7, program your device according to your life rhythm for greater comfort & savings (F127)
- Class II and IP 24 protection with dual electric insulation for ultimate safety
- Sheathed heating element with an aluminium diffuser (safe, silent and long-lasting)
- Automatic over heat safety device

## **SAVINGS**

- High-precision electronic thermostat
- Up to 25% energy savings\* (F127)
- ErP-ready\*\*

## **USER-FRIENDLINESS**

 Easy to install: H-shaped vertical support, which can also be used as an installation template

#### F127

- Ergonomic LCD digital controls
- 2 modes: Manual/Prog

## F117:

- Mode setting cursor and control knob
- 5-mode switch: Comfort, Eco, Frost-free, Off, Programme

## **DESIGN**

- Front air outlet wings
- Colour: white (RAL 9016)





<sup>\*</sup>Compared with a mechanical convector


<sup>\*\*</sup>Depending on models


<sup>\*\*\*</sup> Model types: A: Horizontal / B: Vertical / C: Plinth





## INSTALLATION DIMENSIONS (in mm)





## F117



- 1 Temperature setting knob
- 2 Mode setting slider switch (Shutdown, Anti-frost, Programming, Comfort, Eco)

## F127



- 1 Temperature and active mode display -2 modes: Manual/Prog
- 2 Navigation buttons
- 3 Access to menu/validation
- 4 Energy consumption indicator

## EASY PROG (for F127)

- Manual mode: allows to set-up the device at the desired temperature from OFF to 30°C.
- Prog mode: allows to set up to 3 periods of Comfort temperature by day (24h) over 7 days. Possibility to copy a daily programme on other days of the week.

## F117/F127

TECHNICAL DATA							
OUTPUT (W)	DIMENSIONS (mm)						NET WEIGHT
	Width (W)	Height (H)	Depth (D)	A	B1	B2	(kg)
500	370	453	103	195	256	158	3.8
1000	447	453	103	269	256	158	4.2
1500	590	453	103	343	256	158	5.5
2000	740	453	103	491	256	158	6.8